



## SPECIAL INK FOR TECNOTOP VARNISHES RANGE

PIGMENTS is mastic pigment designed for pigmentation-coloration of translucent aliphatic topcoat TECNOTOP 2C and TECNOTOP 2CP.

## USES

- Add at the TECNOTOP's component B and mix by shaking mechanically (low speed), for the time necessary to achieve a homogeneously colored mixture.
- Use this mixing ratio: 10 ~ 15%, over the total weight of TECNOTOP.
- For cleaning works, you can use our DESMOPOL
- SOLVENT.
- It comes in RAL colorings.

Cleaning	DESMOSOLVENT
Ratio	10% ~ 20% (depending on color)



## PRESENTATION

Metal tins of 1 kg.

## EXPIRY

12 months each product at temperatures between 5° C and 25° C, provided it is stored in a dry place. Once the tin has been opened, the product must be used immediately.



## HANDLING AND TRANSPORT

Review the Material Safety Data Sheet of this product

PROPERTIES	VALUES
Density	White: $\pm 1,5 \sim 2$ g/cm <sup>3</sup>
Density	Red tile 8004: $\pm 1,1 \sim 1,2$ g/cm <sup>3</sup>
Density	Grey 7042: $\pm 1,0$ g/cm <sup>3</sup>
Density	Blue 5012: $\pm 1,0$ g/cm <sup>3</sup> $\pm 0,1$
Appearance	Pasty
Viscosity	< 5.000 cps
% pigment contents	White: 65%
% pigment contents	Red tile 8004: 52%
% pigment contents	Grey 7042: 50%
% pigment contents	Blue 5012: 45%
Particle size	<20 $\mu$ m

